

4 & 5-TERMINAL SINGLE POSITION METER SOCKETS FOR CUSTOMER-OWNED STREET LIGHTING

	<u>Service Application</u>		<u>Reference</u>
1Ø	3-Wire	240/480 Volts (grounded)	0-200 Amperes
			M-11

Supplier	Socket Catalog Numbers			5th Terminal* Catalog No.
	4-Terminal	5-Terminal		
	240/480 Volts, 1Ø (Rated 600 Volts)	240 Volts, 1Ø (Rated 300 Volts)	240 Volts or 480 Volts, 1Ø (Rated 600 Volts)	
Cutler-Hammer	UHT-RS213B-CH UT-H4213_-CH UTE4213_-CH			
Landis & Gyr/ Siemens (5)	HQ4G Series CQ4 Series UAT317-_P UAT417-_P	CQ5 Series HQ5 Series UAT317-_P (1) UAT417-_P (1)	CQ5 Series HQ5 Series	(1) 659-0121
Midwest	UHT-RS213B-MEP UT-H4213_-MEP			
Milbank	U1773 U9550	U1773 (2)	U1773 (2)	(2) K5T
Murray	RH173CR (4)	RS192AX (3)		(3) RX012
Square-D	UHT-RS213B-SQD UT-H4213_-SQD			

*The fifth terminal must be in the 9:00 position.

- (1) thru (3) see 5th Terminal Catalog Number column.
- (4) The 5th terminal shall be removed.
- (5) Add "S" prefix for Siemens.

TEMPORARY SERVICE ASSEMBLIES WITH OVERHEAD SERVICE ENTRANCE

	<u>Service Application</u>		<u>Reference</u>
1Ø	3-Wire	120/240 Volts	0-100 Amperes
			O-16

Supplier	Socket Catalog Numbers		
	120/240 Volts, 1Ø		
	60 Amp.	70 Amp.	200 Amp
Cutler-Hammer			MB816P200STD
Midwest	R038G (1,2) R038C010 (1,3)	R055G (1,2) R055C010 (1,3)	

- (1) MSB9 barrier strip required.
- (2) GFI circuit breaker
- (3) GFI outlet