

4-TERMINAL SINGLE AND MULTI-POSITION METER SOCKETS WITH DIRECT BURIED UNDERGROUND SERVICE LATERAL

	Service Application		Reference
1Ø	3-Wire	120/240 Volts	M-17
		0-200 Amperes	

Supplier	Socket Catalog Numbers		
	100 Amp./Pos.	200 Amp./Pos.	
	Multi-Position*	Single Position	Multi-Position*
Cutler-Hammer		UHT-RS213A-CH UT-H4213A-CH UTE4213A-CH	1009613-CH (2 Pos.) (6) <u>200A</u> 1009614-CH (3 Pos.) (6) <u>270A</u> 1009615-CH (4 Pos.) (6) <u>350A</u> 1009616-CH (5 Pos.) (6) <u>400A</u> 1009617-CH (6 Pos.) (6) <u>400A</u>
Landis & Gyr/ Siemens (5)	UA2311-_P (2 Pos.) 200A UA3311-_P (3 Pos.) 200A UA4311-_P (4 Pos.) 200A	HQ-4GU-40404 CQ-4U-40604 UAT417-_P (1)	UA2717-_P (2 Pos.) 200A UA3717-_P (3 Pos.) (2) <u>270A</u> UA4719-_P (4 Pos.) (2) <u>270A</u> UA5719-_P (5 Pos.) (2) <u>270A</u> UA6719-_P (6 Pos.) (2) <u>270A</u>
Midwest		LTU276-BA LQRLPU414-12BA UHT-RS213A-MEP UT-H4213A-MEP	1009613-MEP (2 Pos.) (6) <u>200A</u> 1009614-MEP (3 Pos.) (6) <u>270A</u> 1009615-MEP (4 Pos.) (6) <u>350A</u> 1009616-MEP (5 Pos.) (6) <u>400A</u> 1009617-MEP (6 Pos.) (6) <u>400A</u>
Milbank	L572 (2 Pos.) 200A L573 (3 Pos.) 200A L574 (4 Pos.) 200A L575 (5 Pos.) 225A L576 (6 Pos.) <u>270A</u>	U9551 U1773	U2872 (2 Pos.) (3)(4) <u>200A</u> U2873 (3 Pos.) (3)(4) <u>270A</u> U2874 (4 Pos.) (3)(4) <u>360A</u> U2875 (5 Pos.) (3)(4) <u>400A</u> U2876 (6 Pos.) (3)(4) <u>400A</u>
Murray		RH173CR RS192A (1)	
Square-D		UHT-RS213A-SQD UT-H4213A-SQD	1009613-SQD (2 Pos.) (6) <u>200A</u> 1009614-SQD (3 Pos.) (6) <u>270A</u> 1009615-SQD (4 Pos.) (6) <u>350A</u> 1009616-SQD (5 Pos.) (6) <u>400A</u> 1009617-SQD (6 Pos.) (6) <u>400A</u>

***The main bus ampere rating is indicated for each multi-position listing. The underlined rating is restricted due to the largest service lateral that can be terminated in the unit.**

- (1) Use coverplate 38595-1 when required.
- (2) Use coverplate 56933 when required to cover hub opening, 2 required for 5 and 6 pos. sockets.
- (3) S2291-TO pedestal raceway required.
- (4) K1539 set screw connector kit required.
- (5) Add "S" prefix for Siemens.
- (6) Wiring trough required; 36" trough: Catalog No. 1008934-CH, 1008934-MEP or 1008934-SQD
54" trough: Catalog No. 1008845-CH, 1008845-MEP or 1008845-SQD
18" extension kit if required; Catalog No. 1009618-CH, 1009618-MEP or 1009618-SQD